

Digital Indicator ID-S 12,7mm, 0,001mm, Lug Back Item number: 543-790



Description


This is a standard model of indicator that is reliable and easy to use. The ABSOLUTE Digimatic Indicator ID-S offers you the following benefits:

- The ABSOLUTE sensor means you don't have to carry out origin setting every time you power it on, saving you time and hassle.
- You can access all functions by using the large, user-friendly buttons on the front of the indicator.
- Large character height of 9 mm provides good readability.
- Exceptional battery life.

Features

No.	
Lug back plate:	
Range:	12,7 mm
Digital step:	0,001 mm
Max. Permissible Error E MPE:	0,003 mm
H MPE (Hysteresis):	0,002 mm
R MPE (Repeatability):	0,002 mm
Type:	EN ISO Standard
Measuring force:	≤ 1,5 N
Protection:	IP42
Mass:	150 g
Display:	LCD, character height 9 mm
Max. response speed:	Unlimited
Alarm:	Low voltage, counting value composition error
Stem Ø:	8 mm
Contact point:	Carbide ball, thread M 2.5 x 0.45 mm
Battery life:	approx. 18000 hours (0.001 mm type), approx. 20000 hours (0.01 mm type)
Power supply:	1 battery SR-44
Data output:	Yes
ON/OFF:	Yes
ORIGIN (ABS-Zero):	Yes
Counting direction switchable:	Yes
Digital/Analog:	Digital
Inch-Metric:	Metric
Delivered:	Including 1 battery

Dimensions



Spare parts

Consumable spares:



Battery SR44 1.5V
938882



Contact Element Ball Point, M2,5x0,45
7,3mm Length, Carbide, Metric
901312