


# IBR APPROVED TRANSPARENT TUBULAR LEVEL GAUGE "TTGB"

*Simple, low cost and reliable gauge for direct reading of clean liquid levels for boiler applications.*



**IBR**



**Schematic Diagram**

## SPECIFICATIONS

Gauge Glass	: Tempered borosilicate 19 mm heavy wall
End Block MOC	: CS SA516 Gr.70, SS316
End Block Type	: Integral offset needle valve with auto ball check
Auto ball Check MOC	: SS316
Guards	: CS, SS304 'C' channel with MS protection tube for glass
Packing	: PTFE
Gland MOC	: CI, SS316
Process Connection MOC	: CS SA516 Gr.70, SS316, CS A105 (BUTT weld /SW connection)
Process Connection	: ¾", 1" x ASME 150# or 300# RF Flange or BUTT Weld or Socket Weld (M) (3000#)
Vent & Drain MOC	: CS SA516 Gr.70 or SS316
Vent	: ¾" BSPT/ NPT plug or ½" socket weld needle valve
Drain	: ½" BSPT/ NPT plug or needle valve or ½" SW needle valve
Scale MOC	: Polycarbonate (screen printed) or SS304 (etched)
Scale Calibration	: mm (LC= 5 mm)
CC Distance	: 300 to 1500 mm in single section
Visibility	: CC distance – 175 mm
Max Temperature	: 200 °C
Working Pressure	: 5 kg/cm <sup>2</sup>
Max Test Pressure	: 10 kg/cm <sup>2</sup>

## APPLCATIONS

Boiler Drum, Blow Down Tanks, Dearator Tanks, Boiler Feed Water Tank, Soft Water Service Tanks

## MODEL IDENTIFICATION

TTGB -							
<b>1. MOC (End Block &amp; Vent/Drain)</b>							
CS SA516	B						
SS316	S						
Others	O						
<b>2. Guards</b>							
CS 'C' Channels with MS protection tube for glass		1					
SS304 'C' Channels with MS protection tube for glass		2					
Others		0					
<b>3. Gland MOC</b>							
CI			I				
SS316			S				
<b>4. Process Connection MOC</b>							
CS SA516				B			
SS316				S			
CS A105 (BUTT weld/ Socket Weld Connection)				A			
Others				O			
<b>5. Process Connection Size and type</b>							
¾" NB ASME 150# RF Flange					A		
¾" NB ASME 300# RF Flange					B		
1" NB ASME 150# RF Flange					C		
1" NB ASME 300# RF Flange					D		
¾" Socket Weld (M) 3000#					E		
1" Socket Weld (M) 3000#					F		
¾" BUTT Weld					G		
1" BUTT Weld					H		
Others					O		
<b>6. Vent &amp; Drain Size &amp; Type</b>							
¾" BSPT Plug x ½" BSPT Plug						A	
¾" NPT Plug x ½" NPT Plug						B	
¾" BSPT Plug x ½" BSPT Needle Valve						C	
¾" NPT Plug x ½" NPT Needle Valve						D	
½" SW Needle Valve x ½" SW Needle Valve						E	
Others						O	



7. Calibrated Scale	
Without	W
Polycarbonate in mm (LC= 5 mm)	1
SS304 in mm (LC= 5 mm)	2
Others	0

## ORDERING INFORMATION

Model No x Liquid x Operating Temperature & Pressure

**PUNE TECHTROL PRIVATE LIMITED**

CIN: U31909PN1997PTC063403



Regd. & Sales: S-18, MIDC Bhosari, Pune - 411026, India  
+91-20-66342900 | ho@punetechtrol.com

Works: J-52/7, MIDC Bhosari, Pune - 411026, India  
+91-20-67313600 | www.punetechtrol.com