

APPLICATIONS

- Liquid & gaseous mediums
- Corrosive environments
- Oil & Gas applications
- Chemical & Petrochemical
- Food & Beverages
- Nuclear power plants

FEATURES

- All SS measuring system
- Socket-case, direct welded
- Threaded / Flanged connection
- External zero adjustment



SCHAFFER DIAPHRAGM PRESSURE GAUGE, ZIPL16-2

DESCRIPTION

General

Design : EN 837-3

Accuracy : $\pm 1.6\%$ of full scale

Ambient temperature : $-40 \dots +65^{\circ}\text{C}$

Service temperature : 100°C max.

Pressure limits : Steady pressure up to FS value
Fluctuating pressure up to 90% of FS value

Weld joints : TIG argon arc welding

Material of construction

Sensing element : Diaphragm

Case & Ring material : AISI 304 SS (Bayonet type) **Top chamber :** AISI 304 SS-Sheet Metal

Diaphragm : AISI 316 SS / Monel / Hastelloy C-276

Bottom chamber : AISI 316 SS / Monel/Hastelloy C-276 - Sheet Metal

Movement mechanism : AISI 304 SS

Dial : Aluminum, black graduation on white background

Pointer : Micro-adjustable, aluminum, black powder coated

Gaskets, Blow-off disc & filling plug : Neoprene / NBR

Window : Sheet glass / Shatterproof Safety Glass

Standard version

Dial size : DN100 / DN150

Range : $-1 \dots 0 \dots 25$ bar [Standard] / $60 \dots 600$ mbar [Low pressure]
 $6 \dots 40$ mbar [Very low pressure]

Mounting pattern : Direct, Bottom connection

Process connection : $\frac{1}{2}$ " NPT (M) / $\frac{1}{2}$ " BSP (M)

Ingress protection : IP 54

Execution : Dry

Temperature effect


When temperature of the measuring system deviates from reference temperature ($+20^{\circ}\text{C}$) :
max error $\pm 0.4\%$ / 10K of true scale value.

SCHAFFER DIAPHRAGM PRESSURE GAUGE-ECO DESIGN

ZIPL16-2



DIMENSIONAL DRAWING



ORDERING CODE

MODEL						ZIPL16-2		
ZIPL16-2 Schaffer Diaphragm Pressure Gauge - ECO Design								
DIAL SIZE						D4		
D4	4" / 100 mm		D6	6" / 150 mm				
MOUNTING						M1		
M1	Direct bottom							
CONNECTION						P08		
P04	¼" NPT (M)		P08	½" NPT (M)			P20	M20 X 1.5 mm (M)
P03	¼" BSP (M)		P05	3/8" BSP (M)		P07	½" BSP (M)	
CASE FILLING						F1		
F1	Dry							
WETTED PARTS						S01		
S01	AISI 304 SS		S02	AISI 316 SS			S05	Monel
S10	Hastelloy C-276							
INGRESS PROTECTION						I1		
I1	IP 65							
RANGE						0-1 bar		
0-1 bar	Please mention range required with the measurement unit [TGI offer in all types of National & International measurement units, e.g. kg/cm², psi, kPa, etc. with single or dual scales]							
OTHER OPTIONS						E16/E27		
E16	5 - point calibration certificate		E31	Custom designed dial			E32	Dial tag marking
E28	SS tag plate, AISI 316 SS		E27	SS tag plate, AISI 304 SS			E33	AISI 316 SS case & ring
E20	Cleaned for Oxygen service		E10	Over range protection 1.5xFS				

Ordering Example : ZIPL16-2-D4.M1.P08.F1.S01.I1/0-1 bar/E16/E27

